

## CLAIMS

1. A method for processing data including an image for presentation on a display having a first display portion and a second display portion, the first and second display portions separated by a visible seam having a location and a width, the method comprising the steps of:
- 5
- locating a position on at least one of the first and second display portions for displaying the image; and
- displaying the image in said position such that, when said position extends beyond one of the display portions and onto a next one of the display portions, a portion of the image corresponding to the location of the visible seam is omitted.
- 10
2. The method of claim 1, wherein the locating step comprises the step of repeatedly moving the image back and forth perpendicular to the visible seam during a time period, such that the portion of the image corresponding to the position of the visible seam differs with time, thereby allowing a display of potentially omitted portions of the image during part of the time period.
- 15
3. The method of claim 1, wherein the locating step comprises the step of moving the image back and forth perpendicular to the visible seam, in response to a user input through a user interface.
- 20
4. The method of claim 1, wherein the displaying step comprises the step of scaling the image for presentation on a display surface having a size and aspect ratio compatible with the first and second display portions aligned adjacent to one another and separated by more than the width of the visible seam.
- 25

5. The method of claim 1, wherein the locating step further comprises the steps of:

processing the image to identify predetermined important features of the image; and

5 locating the image such that the predetermined important features do not fall within the portion of the image corresponding to the position of the visible seam.

6. The method of claim 1, wherein the locating step comprises the step of  
10 positioning the image wholly in one of the first and second display portions.

7. The method of claim 1,  
wherein the data also includes text, and  
wherein the method further includes the step of wrapping the text to  
15 fit into areas of the first and second display portions not used for displaying the image.

8. The method of claim 1,  
wherein the data includes attributes for controlling at least one of  
20 scaling and placement of the image on the display and identifying important areas of the image, and

wherein the locating step comprises the step of scaling and locating the image and protecting the important areas in accordance with the attributes.

09855388-051501  
T05150-09855388

9. An apparatus for processing data including an image for presentation on a display having a first display portion and a second display portion, the first and second display portions separated by a visible seam having a location and a width, the apparatus comprising:

5                   an input interface for accepting the data;  
                   a processor coupled to the input interface for processing the data;  
 and

                  an output interface coupled to the processor for outputting the processed data,

10           wherein the processor is programmed to:

                  determine a location of a position on at least one of the first and second display portions for displaying the image; and

                  process the data for displaying the image in said position such that, when said position extends beyond one of the display portions and onto a next one of the display portions, a portion of the image corresponding to the location of the visible seam is omitted.

15

10. The apparatus of claim 9, wherein the processor is further programmed to repeatedly move the image back and forth perpendicular to the visible seam during a time period, such that the portion of the image corresponding to the position of the visible seam differs with time, thereby allowing a display of potentially omitted portions of the image during part of the time period.

20

11. The apparatus of claim 9, wherein the processor is further programmed to scale the image for presentation on a display surface having a size and aspect ratio compatible with the first and second display portions aligned adjacent to one another and separated by more than the width of the visible seam.

25

12. The apparatus of claim 9, wherein the processor is further programmed to:

process the image to identify predetermined important features of the image; and

5                    locate the image such that the predetermined important features do not fall within the portion of the image corresponding to the position of the visible seam.

13. The apparatus of claim 9,

10                    wherein the data also includes text, and

wherein the processor is further programmed to wrap the text to fit into areas of the first and second display portions not used for displaying the image.

15                    14. The apparatus of claim 9,

wherein the data includes attributes for controlling at least one of scaling and placement of the image on the display and identifying important areas of the image, and

20                    wherein the processor is further programmed to scale and locate the image and protect the important areas in accordance with the attributes.

09855333-054504  
T09T50"9855333

15. A electronic device for processing data including an image, comprising:  
an input interface for accepting the data;  
a processor coupled to the input interface for processing the data;

and

5 a display coupled to the processor for displaying the processed data,  
the display having a first display portion and a second display portion, the first  
and second display portions separated by a visible seam having a location and a  
width;

wherein the processor is programmed to:

10 determine a location of a position on at least one of the first and  
second display portions for displaying the image; and

process the data for displaying the image in said position such that,  
when said position extends beyond one of the display portions and onto a next  
one of the display portions, a portion of the image corresponding to the location  
15 of the visible seam is omitted.

16. The electronic device of claim 15, wherein the processor is further  
programmed to repeatedly move the image back and forth perpendicular to the  
visible seam during a time period, such that the portion of the image  
20 corresponding to the position of the visible seam differs with time, thereby  
allowing a display of potentially omitted portions of the image during part of the  
time period.

17. The electronic device of claim 15, wherein the processor is further  
25 programmed to scale the image for presentation on a display surface having a size  
and aspect ratio compatible with the first and second display portions aligned  
adjacent to one another and separated by more than the width of the visible seam.

process the image to identify predetermined important features of the image; and

19. The electronic device of claim 15,  
 wherein the data also includes text, and  
 wherein the processor is further programmed to wrap the text to fit  
 into areas of the first and second display portions not used for displaying the  
 image.

12